


# Product Data Sheet





## Sensors and Actuator

- ❖ Product Description- M12 Male Straight X Code to M12 Male Straight X Code Pvc Shielded Green Cable
- ❖ MPN-2412-9696-9088-814-XXXX-Gn
- ❖ Series –M12 X coded

### Illustration



-Colour customization available based on MOQ



Product may differ from image



Product Datasheet Rev.No-00 Effective date-24-11-2025

The information in this product PDF has been compiled with the utmost care  
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220  
India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com; +91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL  
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

## Product Data Sheet

### Sensors and Actuator

Technical Data	
Operating voltage	300V AC/DC*
Rated Surge Voltage	2.5 kV
Operating current per contact AMP	Max. 4 A
Connection type head A	Male Connector, M12 Straight, 8 Pin, X coded
Connection type head B	Male Connector, M12 Straight, 8 Pin, X coded
Protection	IP67, IP68, IP69
Housing Material	TPU
Locking nut material	Brass, Nickel plated
LED display	No
Connector colour	Black
Tightening torque	0.6 Nm

Electrical Data	
Overvoltage category	II
Contact resistance	$\leq 5 \text{ m}\Omega$
Insulation resistance	$\geq 100 \text{ m}\Omega$
Test voltage	$\geq 3000 \text{ V}$
Conductor material	Bare Cu litz wires
Max. conductor resistance	Max. 57 $\Omega$ /km (at 20 °c)
Nominal voltage	$\leq 300 \text{ v}$

Mechanical Data	
Insertion/withdrawal cycles	$\geq 100$

Product properties	
Application	Up to 100 Mbit ethernet (Standard TIA 568-B) & Profinet
Partly UV-resistant	in accordance with DIN EN ISO 4892-2-A
Flammability rating According to UL 94	HB

Product Datasheet Rev.No-00 Effective date-24-11-2025

The information in this product PDF has been compiled with the utmost care  
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220  
India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com; +91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL  
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

## Product Data Sheet

### Sensors and Actuator

#### General Data

<b>Standards</b>	IEC-61076-2-101 (M12)
<b>Mounting method</b>	Inserted, tightened.
<b>Pin Contact</b>	CuZn
<b>Housing contact</b>	CuSn
<b>Material (contact surface)</b>	Au
<b>Pollution Degree</b>	3
<b>Stripping length (jacket)</b>	20 mm (If required)
<b>Temperature range</b>	-25.... +90°C

#### Cable Data

<b>Cable Type</b>	CAT6A PVC
<b>Cable weight</b>	50 g/m
<b>Diameter (core)</b>	8*0.14 mm <sup>2</sup> .
<b>AWG</b>	similar to AWG 26
<b>Material (wire isolation)</b>	PP
<b>Material property (wire isolation)</b>	Halogen-, CFC-, cadmium-, silicone- and lead-free
<b>Colour/numbering of wires</b>	White/Orange, Orange, White/Green, Blue, White/Blue, Green, White/ Brown, Brown.
<b>Stranding combination</b>	4 wires twisted
<b>Shield</b>	Yes
<b>Shielding</b>	Tin braided
<b>Optical shield covering</b>	Min 85%
<b>Material (jacket)</b>	CAT6A PVC
<b>Outer-Ø (jacket)</b>	6.20 ±0.2 mm <sup>2</sup>
<b>Colour (jacket)</b>	Green
<b>Chemical resistance</b>	good resistance to oil, gasoline and chemicals (EN 60811-404)
<b>Thermal resistance</b>	flame retardant UL 1581 Section 1090 (H), CSA FT2 / IEC 60332-2-2
<b>Temperature range (fixed)</b>	-40...+80 °C, (+105 °C. at max. 10 000 operating hours)
<b>Temperature range (mobile)</b>	-25...+90 °C, (+105 °C. at max. 10 000 operating hours)
<b>Bend radius (fixed)</b>	8× outer Ø
<b>Bend radius (moving)</b>	12× outer Ø
<b>No. of bending cycles (C-track)</b>	10 Mio. (25 °C)
<b>Acceleration (C-track)</b>	Max. 10 m/s

Product Datasheet Rev.No-00 Effective date-24-11-2025

The information in this product PDF has been compiled with the utmost care  
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220  
India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com;+91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL  
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

## Product Data Sheet

### Sensors and Actuator

<b>Torsion stress</b>	±180°/m
<b>No. of torsion cycles</b>	max.2 Mio(25°c)
<b>Torsion speed</b>	35 cycle/min

### Approvals

UL  
CE  
cULus  
RoHS

Note: This product has been manufactured by the following Class-I, Class-II and class-III **IPC** standards

To understand the MPN please refer the below Table

<b>2412-9696-9088-814-XXXX-Gn</b>	
24	Series
12	M12 connector
96	Male straight
96	Male straight
9	X code
08	CAT6A PVC Shielded
8	8 Pole connectors
8	8 Core cable
14	0.14 mm <sup>2</sup> (Core size)
XXXX	Cable length as per customer requirement
Gn	Green Cable

Product Datasheet Rev.No-00 Effective date-24-11-2025

The information in this product PDF has been compiled with the utmost care  
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220  
India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com; +91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL  
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.