


Product Data sheet



Industrial Ethernet Cable – Extension Cable

- ❖ Product description- RJ45 Male 0° / RJ45 Male 0° 8P8C CAT 6A FRLSH Shielded Green Cable
- ❖ MPN- 2445-9696-0028-814-XXXX-Gn
- ❖ Series –RJ45 Cord Set

Illustration



- ❖ -Colour customization available based on MOQ



Product may differ from image



Product Datasheet Rev.No-01 Effective date-26-08-2026

The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220
India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com; +91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

Product Data sheet

Industrial Ethernet Cable – Extension Cable

Technical Data	
Operating voltage	60V AC/DC*
Rated Surge Voltage	1 kV
Operating current per contact AMP	Max. 1.5 A
Connection type head A	RJ45, 8-Pin, Male Straight,
Connection type head B	RJ45, 8-Pin, Male Straight,
Protection	IP20
Housing Material	TPU
LED display	No
Connector colour	Transparent

Electrical Data	
Overvoltage category	II
Contact resistance	$\leq 20 \text{ m}\Omega$
Insulation resistance	$\geq 500 \text{ m}\Omega$
Test voltage	$\geq 1500 \text{ V}$
Conductor material	Cu wire
Max. conductor resistance	Max. 140 Ω/km (at 20 °c)
Nominal voltage	$\leq 600 \text{ v}$
Frequency Range	Up to 500 MHz

Mechanical Data	
Insertion/withdrawal cycles	≥ 750
Insertion force	20 N max
Pull Retention force	50 N min
Durability	750 Mating and Unmating cycles

Product properties	
Application	Ethernet, Data transmission
Partly UV-resistant	in accordance with DIN EN ISO 4892-2-A
Flammability rating According to UL 94	V2

Product Datasheet Rev.No-01 Effective date-26-08-2026

The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220
India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com; +91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

Product Data sheet

Industrial Ethernet Cable – Extension Cable

General Data	
Category	CAT6A
Mounting method	Inserted
Pin Contact	CuZn Gold plated
Housing contact	CuZn
Material (contact surface)	Au
Pollution Degree	3
Transmission Speed	10 Gbps
Temperature range	-25.... +105°C

Cable Data	
Cable Type	FR-LSH
Cable weight	65 g/m
Conductor Cross Section	4*2*0.14 mm².
AWG	Similar to AWG 26
Material (wire isolation)	PP
Material property (wire isolation)	Halogen-, CFC-, cadmium-, silicone- and lead-free
Colour/numbering of wires	White/Orange, Orange, White/Green, Blue, White/Blue, Green, White/ Brown, Brown
Twisted Pairs	2 Cores to the pair
Shield	Yes
Shielding	Tin braiding
Optical shield covering	Min 85%
Material (jacket)	FR-LSH
Outer-Ø (jacket)	6.20 ±0.2mm
Colour (jacket)	Green
Chemical resistance	Good resistance to oil, gasoline and chemicals (EN 60811-404)
Thermal resistance	Flame retardant UL 1581 Section 1090 (H), CSA FT2 / IEC 60332-2-2
Temperature range (fixed)	-40...+80 °C, (+105 °C. at max. 10 000 operating hours)
Temperature range (mobile)	-25...+80 °C, (+105 °C. at max. 10 000 operating hours)
Bend radius (fixed)	5× outer Ø
Bend radius (moving)	10× outer Ø

Product Datasheet Rev.No-01 Effective date-26-08-2026

The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220
India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com; +91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.

Product Data sheet

Industrial Ethernet Cable – Extension Cable

Drag chain (fixed & moving)	12× outer Ø
No. of bending cycles (C-track)	3 Mio
Acceleration (C-track)	Max. 2.4 m/s
Torsion stress	±180 °/m
No. of torsion cycles	1 Mio
Torsion speed	35 cycle/min

Approvals

UL
CE
cULus
RoHS

Note: This product has been manufactured by the following Class-I, Class-II and class-III **IPC** standards

To understand the MPN please refer the below table

2445-9696-0028-814-XXXX-Gn	
24	Series
45	RJ45 Connector
9	Male
6	Straight
9	Male
6	Straight
02	CAT 6A FRLSH Shielded
8	8 Pole Connectors
8	8 Core Cable
14	0.14 mm ² (Core size)
XXXX	Cable length as per customer requirement
Gn	Green Cable

Product Datasheet Rev.No-01 Effective date-26-08-2026

The information in this product PDF has been complied with the utmost care
Liability for the correctness completeness and topicality of the information is restricted to gross negligence.

Office Address: Ground Floor Plot No, G-8/7, Ranjangaon Industrial Area Shirur Road Karegaon, Ranjangaon MIDC, Pune Maharashtra-412220
India. Contact- info@leiindias.com; sales@leiindias.com; www.leiindias.com; +91-7448296005; +91-020-66205306 GST No-27AACCL5628E1ZL
Factory Address: 2347/B Wagholi Warehouse, Pune Nagar Road, Wagholi, Pune- 412207, Maharashtra, India.