Product data sheet

Power connectors



Contact arrangement (Plug-in side)

2

3 4 5

6

8

χ Y 3,60 4,30

5,55 1,00

4,90 -2,80 1,90 -5,30 -1,90 -5,30 -4,90 -2,80 -5,55 1,00

-3,60 4,30

 9
 0,00
 4,50

 10
 1,90
 1,00

 11
 0,00
 -2,20

12 -1,90 1,00

Product description

M23 male panel mount connector, Contacts: 12, shielding is not possible, solder, IP67, central lock

Scale drawing

0-Ring

13,5

. 9d

6

Area Order number M23 series 623 99 4607 20 12

Illustration



Technical data

General values

Connector design Connector locking system Termination Arrangement of contacts Wire gauge (mm) Wire gauge (AWG) Upper limit temperature Lower limit temperature Customs tariff number Packaging Unit

male panel mount connector screw solder clockwise max. 1.00 mm² max. 17 125 °C – 20 °C 85369010 40

Vibrationsbremse

20,3

M23 x 1

Electrical values

SW 24mm

Ø 26

Rated current (40 °C) Rated voltage Rated impulse voltage Pollution degree Overvoltage category Insulating material group Insulation resistance EMC compliance Degree of protection Mechanical operation

Material

Contact material Contact plating Contact body material Housing material REACH SVHC

8 A 150 V 1500 V 3 Ш Ш $\geq 10^{10}\,\Omega$ shielding is not possible IP67 > 50 Mating cycles

CuZn (brass) Au (gold) PBT/PA66 Zinc die-cast nickel-plated CAS 7439-92-1 (Lead)

Product data sheet

Power connectors



Product description

M23 male panel mount connector, Contacts: 12, shielding is not possible, solder, IP67, central lock

Area Order number M23 series 623 99 4607 20 12

Security notices

The connector must not be connected or separated under load. Non-observance and incorrect use can result in personal injury.

The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.

Connectors with degree of protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the connectors must be separately protected against corrosion. For further information about IP degrees of protection refer to 'Technical support' in the Download Centre.