Product data sheet

Power connectors




Product description M23 square male panel mount connector, Contacts: 16, shielding is not possible, solder, IP67, back mounting


M23 series 623 Order number 99 4611 80 16

Illustration





Contact arrangement (Plug-in side)



Technical data

General values

Connector design

Connector locking system Termination Arrangement of contacts Wire gauge (mm) Wire gauge (AWG) Upper limit temperature Lower limit temperature Customs tariff number Packaging Unit

square male panel mount

connector screw solder clockwise max. 1.00 mm² max. 17 125 °C – 20 °C 85369010

Electrical values

Rated current (40 °C) Rated voltage 150 V Rated impulse voltage 1500 V Pollution degree Overvoltage category Ш Insulating material group Ш $\geq 10^{10} \, \Omega$ Insulation resistance shielding is not possible EMC compliance

Degree of protection

Mechanical operation > 50 Mating cycles

Material

CuZn (brass) Contact material Contact plating Au (gold) PBT/PA66 Contact body material Housing material Zinc die-cast nickel-plated REACH SVHC CAS 7439-92-1 (Lead)

Product data sheet

Power connectors



Product description M23 square male panel mount connector, Contacts: 16, shielding is not possible, solder, IP67, back mounting

Area **M23 series 623**Order number **99 4611 80 16**

Security notices

The connector must not be connected or separated under load. Non-observance and incorrect use can result in personal injury.

The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.

Connectors with degree of protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the connectors must be separately protected against corrosion. For further information about IP degrees of protection refer to 'Technical support' in the Download Centre.