Product data sheet

Power connectors



Product description M23 female panel mount connector, Contacts: 16, shielding is not possible, solder, IP67, central lock


Area **M23 series 623**Order number **99 4612 20 16**

Illustration



Vibrationsbremse 0-Ring Ø 26

Contact arrangement (Plug-in side)



Technical data

General values

Connector design
Connector locking system
Termination
Arrangement of contacts
Wire gauge (mm)
Wire gauge (AWG)
Upper limit temperature
Lower limit temperature
Customs tariff number
Packaging Unit

female panel mount connector screw solder clockwise max. 1.00 mm² max. 17 125 °C – 20 °C 85369010

Electrical values

Rated current (40 °C) Rated voltage 150 V Rated impulse voltage 1500 V Pollution degree Overvoltage category Ш Insulating material group Ш $\geq 10^{10} \, \Omega$ Insulation resistance shielding is not possible EMC compliance Degree of protection Mechanical operation > 50 Mating cycles

Material

Contact material CuSn (bronze)
Contact plating Au (gold)
Contact body material PBT/PA66
Housing material Zinc die-cast nickel-plated
REACH SVHC CAS 7439-92-1 (Lead)

Product data sheet

Power connectors



Product description M23 female panel mount connector, Contacts: 16, shielding is not possible, solder, IP67, central lock

Area **M23 series 623**Order number **99 4612 20 16**

Security notices

The connector must not be connected or separated under load. Non-observance and incorrect use can result in personal injury.

The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.

Connectors with degree of protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the connectors must be separately protected against corrosion. For further information about IP degrees of protection refer to 'Technical support' in the Download Centre.