

# Product data sheet

## Miniature connectors




|                     |  |
|---------------------|--|
| Product description | <b>M16 IP67 cable connector, Contacts: 2, 4.0 - 6.0 mm, shieldable, solder, IP67, UL</b> |
| Area                | <b>M16 IP67 series 423</b>   |
| Order number        | <b>99 5101 15 02</b>   |


### Illustration



### Scale drawing



### Contact arrangement (Plug-in side)



|   | X     | Y    |
|---|-------|------|
| 1 | 3,50  | 0,00 |
| 2 | -3,50 | 0,00 |

You can find the component part drawing and assembly instructions on the next page.

## Technical data

### General values

|                          |                           |
|--------------------------|---------------------------|
| Connector design         | cable connector           |
| Connector locking system | screw                     |
| Termination              | solder                    |
| Wire gauge (mm)          | max. 0.75 mm <sup>2</sup> |
| Wire gauge (AWG)         | max. 18                   |
| Cable outlet             | 4.0 - 6.0 mm              |
| Upper limit temperature  | 95 °C                     |
| Lower limit temperature  | - 30 °C                   |
| Customs tariff number    | 85369010                  |
| Packaging Unit           | 20                        |

### Cable data

|            |    |
|------------|----|
| Approval 1 | UL |
|------------|----|

### Electrical values

|                           |                      |
|---------------------------|----------------------|
| Rated current (40 °C)     | 7 A                  |
| Rated voltage             | 250 V                |
| Rated impulse voltage     | 1500 V               |
| Pollution degree          | 1                    |
| Overvoltage category      | I                    |
| Insulating material group | III                  |
| Insulation resistance     | ≥ 10 <sup>10</sup> Ω |
| EMC compliance            | shieldable           |
| Degree of protection      | IP67                 |
| Mechanical operation      | > 500 Mating cycles  |


### Material

|                       |   |
|-----------------------|---|
| Contact material      | CuZn (brass)  |
| Contact plating       | Ag (silver)   |
| Contact body material | PBT (UL94 V-0)  |
| REACH SVHC            | CAS 96-45-7<br>(Imidazolidine-2-thione)<br>CAS 7439-92-1 (Lead) |

Product description **M16 IP67 cable connector, Contacts: 2, 4.0 - 6.0 mm, shieldable, solder, IP67, UL**

Area **M16 IP67 series 423**  
Order number **99 5101 15 02**

## Component part drawing




## Assembly instructions / Panel cut-out

### Gerade Version

(Ausführung mit Schirmklemmring)

1. Druckschraube, Klemmkorb, Dichtung, Distanzhülse und ersten Schirmklemmring auffädeln.
2. Litzen abisolieren, Schirm aufweiten und zweiten Schirmklemmring auffädeln.
3. Litzen anlöten, Distanzhülse montieren, die beiden Klemmringe mit dem Schirm zusammenschieben und überstehenden Schirm abschneiden.
4. Übrige Teile gemäß Darstellung montieren.



|                     |  |
|---------------------|--|
| Product description | <b>M16 IP67 cable connector, Contacts: 2, 4.0 - 6.0 mm, shieldable, solder, IP67, UL</b> |
| Area                | <b>M16 IP67 series 423</b>   |
| Order number        | <b>99 5101 15 02</b>   |

## Security notices

The connector must not be connected or separated under load. Non-observance and incorrect use can result in personal injury.

The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.

Connectors used in electrical circuits containing hazardous life parts must only be assembled and used by or under the supervision of persons with the requisite electrotechnical training, taking the applicable regulations and standards into account.

Connectors with degree of protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the connectors must be separately protected against corrosion. For further information about IP degrees of protection refer to 'Technical support' in the Download Centre.

The connector is not suitable for mains voltages. Please observe the pollution degrees and the overvoltage category. For further information refer to 'Technical support' in the Download Centre.

To lock the cable connector to the equipment connector, the threaded ring is tightened until it is 'finger-tight' (approx. 50 cNm).