


Product description **Snap-In IP67 (miniature) female panel mount connector, Contacts: 12, not shielded, solder, IP67, VDE**

Area **Snap-In IP67 (miniature) series 720**  
Order number **99 9136 60 12**


### Illustration



### Scale drawing



### Contact arrangement (Plug-in side)



	X	Y
1	0,00	-3,70
2	-2,62	-2,62
3	-3,70	0,00
4	-2,62	2,62
5	0,00	3,70
6	2,62	2,62
7	3,70	0,00
8	2,62	-2,62
9	1,79	-0,74
10	-0,74	-1,79
11	-1,79	0,74
12	0,74	1,79

You can find the component part drawing and assembly instructions on the next page.

## Technical data

### General values

Connector design	female panel mount connector
Connector locking system	snap
Termination	solder
Wire gauge (mm)	max. 0.25 mm <sup>2</sup>
Wire gauge (AWG)	max. 24
Upper limit temperature	85 °C
Lower limit temperature	- 25 °C
Customs tariff number	85369010
Packaging Unit	100,000

### Cable data

Approval 1	VDE
------------	-----

### Electrical values

Rated current (40 °C)	2 A
Rated voltage	60 V
Rated impulse voltage	800 V
Pollution degree	2
Overvoltage category	II
Insulating material group	II
Insulation resistance	≥ 10 <sup>10</sup> Ω
EMC compliance	not shielded
Degree of protection	IP67
Mechanical operation	> 500 Mating cycles

### Material

Contact material	CuSn (bronze)
Contact plating	Au (gold)
Contact body material	PA (UL94 HB)
Housing material	PA

Product description

Snap-In IP67 (miniature) female panel mount connector, Contacts: 12, not shielded, solder, IP67, VDE


Area

Snap-In IP67 (miniature) series 720


Order number

99 9136 60 12

### Component part drawing



### Assembly instructions / Panel cut-out



Product description	<b>Snap-In IP67 (miniature) female panel mount connector, Contacts: 12, not shielded, solder, IP67, VDE</b>
Area	<b>Snap-In IP67 (miniature) series 720</b>
Order number	<b>99 9136 60 12</b>

## Security notices

The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.

Connectors with degree of protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the connectors must be separately protected against corrosion. For further information about IP degrees of protection refer to 'Technical support' in the Download Centre.